

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 December 2005 (08.12.2005)

PCT

(10) International Publication Number
WO 2005/115604 A1

(51) International Patent Classification⁷: **B01J 8/02**

(21) International Application Number:
PCT/EP2005/003439

(22) International Filing Date: 1 April 2005 (01.04.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
04012231.9 24 May 2004 (24.05.2004) EP

(71) Applicant (for all designated States except US):
METHANOL CASALE S.A. [CH/CH]; Via Giulio
Pocobelli, 6, CH-6900 Lugano-Besso (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FILIPPI, Ermanno**
[IT/CH]; Strada di Gandra, 73, CH-6976 Castagnola (CH).

RIZZI, Enrico [IT/IT]; Via Manzoni, 4, I-22070 Casnate
con Bernate (CO) (IT). **TAROZZO, Mirco** [IT/CH]; Via
L. Piffaretti, CH-6853 LigoRETTO (CH).


(74) Agent: **ZARDI, Marco**; M. Zardi & CO. S.A., Via Pioda,
6, CH-6900 Lugano (CH).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: PLATE-TYPE HEAT-EXCHANGER



(57) Abstract: A plate-shaped heat exchanger (20, 120) for a heat exchange unit (40) of a chemical reactor (60), that advantageously presents a thermal insulation obtained in an unusually simple and reliable manner, has a substantially flattened box-like structure (22), with a substantially parallelepiped, rectangular configuration, defining an internal chamber (24), and comprises an inlet connection (28) and an outlet connection (29) of a heat exchange operating fluid into and from said chamber (24), and a distributor pipe (10, 110) of said operating fluid inside said chamber (24), extended in said structure (22) at a long side (22a) of it, said distributor pipe (10, 110) comprising a first tube (30, 130) and a second tube (32, 132), positioned one inside the other, between said tubes, respectively external tube (30) and internal tube (32, 132), an interspace (30a) being defined in fluid communication, on one side, with said chamber (24) through a plurality of openings (26) provided in the external tube (30, 130) of said distributor pipe (10, 110), and, on the other side, with the internal tube (32, 132) of the same distributor pipe (10, 110), said internal tube (32, 132) being hydraulically connected to said inlet connection (28) for the heat exchange operating fluid.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.